

FEATURES YOU CAN BANK UPON

- A Perfect Match for your Inverter & UPS System: Your Inverter and UPS System have unique circuitry with demands. which cannot be met by just battery. Su-Kam Power Bank Batteries are scientifically built, keeping these every factors in mind. They match your appliances perfectly!
- . Capable of Withstanding Deep Discharge and Overcharge: Only Su-Kam Power Bank Batteries are tough enough to perform under these extreme operating conditions. Thus, they are far more dependable and economical to use. Their capability to withstand deep discharge is due to balanced active material and large electrolyte reserve. Special Lead Alloy Composition ensures low self discharge and resistance to overcharge.
- . Intercell Welding: This is through a partition wall and results in better performance while reducing chances of accidental short-circuiting of cells.



INVEST IN THE BEST

- plates are of pasted type with sturdy construction. Negative plates are designed to match the power and long life of the positive plates. The active material is a blend of oxide, special additive and expanders for long life and • Vent Plugs: The special design vent plug traps the performance.
- PE Separators: Poly-ethylene Separators thus offers the best balanced property spectrum: excellent mechanical and chemical stability as well as good acid availability, low electrical resistance, low pore size & high porosity.
- · Positive & Negative Plates: The positive and negative · Strong Containers/Covers: These are made of high quality polypropylene material with excellent resistance against impact and abrasion, thus providing overall protection against damage.
 - escaping acid vapor and gases to go out, thus significantly reducing evaporation of water from the cell and resulting in reduced water topping requirements of the battery.

Technical Specifications						
SR. NO.	Battery Type	Capacity	Charging Current (Amps) Initial	Maximum Overall Dimensions (mm)		
				Length	Width	Height
1	SIG 135C	135AH	6.5	515	215	250
2	SIG 150C	150AH	7.0	515	215	250
3	SIG 165C	165AH	8.0	520	275	250
4	SIG 190C	190AH	9.5	520	275	250

KNIGHT (Double Trolley) CHETAK (Single Trolley

Note: Specifications are subject to change without prior notion

ided Ad-on-Products



For more details, Please contact