

INVA MASTER

**EXIDE
TUBULAR** >>>

Tubular Batteries for Inverter Application



Mera Inverter Maange Only **INVA**

* Conditions Apply

Features:

- Economical Range
- Rugged Tubular Plates
- Suitable for frequent power outages
- Higher Acid Volume / Ampere-Hour

Dimensions & Capacity

Model	Capacity at 27°C when discharged at C20 upto 1.75 vpc	Dimension (+/- 3mm)			Battery Weights (kg +/- 5%)	
		Length	Width	Height*	Dry Weight	Charged Weight
IM3000	80	410	176	281	18.5	29.7
IM 4000	100	410	176	281	22.0	41.0
IM 4000T	100	500	187	416	29.0	53.8
IM 5000	115	535	222	275	25.8	43.5
IM 7500	135	535	222	275	29.9	47.0
IM 8500	150	535	222	275	32.3	49.1
IM 10000	150	500	187	416	33.2	57.5
IM 15000	180	500	187	416	39.2	65.1
IM 20000	200	500	187	416	41.5	67.0

Statutory Notice:

All batteries contain lead, which is harmful for humans and environment. As per statutory requirements, the used battery must be returned to the authorized dealer, manufacturer or at the designated collection centres.

Authorised Dealer

